SC UPC Simplex
OM1 Multimode PVC 0.9mm -2m(6ft) FOPT
21F1411-2 (7242212)

Product Specification

Fiber Optic Cable

Fiber Type	Single-mode: OS2 (G.652.D / G.657.A1 / G.657.A2)
	Multi-mode: **OM1**(62.5/125), OM2(50(125), [(OM3, OM4) (50/125,Laser Optimization)]
900um/0.9mm Buffer Colour	**Yellow**: SM: OS2 (G.652.D / G.657.A1 / G.657.A2)
	Orange: **OM1**, OM2
	Aqua: OM3, OM4
	Customized : Green,Brown,White,Red,Black,Purple,Rose,Slate
900um/0.9mm Types	**Single Typical: 1 Fiber**
	Bunch Typical: 12 Fibers
	Customized: 4-48 Fibers
Aramid Yarn (2.0/3.0mm)	Aramid yarn is laid over the cable core to serve as peripheral strength member.
Cable Jacket	Main material: **PVC** / LSZH / Plenum (OFNP)
	OD: Simplex: **0.9**/2.0/3.0mm Duplex: 0.9/2.0/3.0mm
Jacket Color	**Yellow**: SM: OS2 (G.652.D / G.657.A1 / G.657.A2)
	Orange: OM1, OM2
	Aqua: OM3, OM4
Cable Length	1m, **2m**, 3m. other lengths on request

Product Specification

Connector

Connector Type	LC, SC, FC, ST, MU, MTRJ, LSH, E-2000
	SC (Subscriber Connector/Square Connector/Standard Connector) Typical Application: Telecom,GPON,EPON,GBIC



Product Specification

Parameter	SC UPC
	OM1 G.652.D/G.657.A1/G.657.A2
Operating Wavelength(nm)	850-1300
Insertion Loss (dB)	≤ 0.3
Return Loss (dB)	≥ 35
Repeatability (dB)	≤ 0.1
Interchangeability (dB)	≤ 0.2
Tensil Strength (N)	≥ 1000
Operating Temperature (℃)	-20 ~ +85
Storage Temperature (℃)	-40 ~ +85

Zion Code	Description
21F1411-2 (7242212)	SC UPC Simplex OM1 Multimode PVC 0.9mm -2m(6ft) FOPT



OEM/ODM service for you

ZION Communication has rich expiriences in producing OEM/ODM cases becaused of Profession R & D team.

- Customized Logo
- Printing on Cable
- Label/PE bag/Carton design
- Different Color & Different Lengths Available