

SC UPC Hot-Melt Fast Connector



Zion Code and Description

Zion Code	Zion Description
7234022	SC UPC Hot-Melt Fast Connector

Product description:

- High cost-effective fiber optic fast connector, which ensure installation quality and efficiency;
- Crimping part adopts original and unique physical design, injected glue, grinding, consumable are unnecessary when installing;
- Embedded fiber optic structure;
- With the feature of high installation quality, high success rate, high installation speed, and etc;
- Can be reusable, easy operation;
- Convenient to carry.

Description

ZION COMMUNICATIONS' Fiber Optic Connector is a reusable passive device used to connect two Optic fibers or Optic cables to form a continuous Optic path. It has been widely used in Optic fiber transmission lines, Optic fiber distribution frames, and Optic fiber testing instruments and meters. It is currently in use. The most Optic passive devices. The Connectors supplied by Hangzhou Zion Communication Co., Ltd. have high flame retardancy, low insertion loss, high durability, and wide operating temperature. It is your best choice.





LC FAST Field Fiber Optic Connector

Characteristics:

Parameter	FC, SC, LC			ST, MU, MTRJ	
	SM (OS2)		MM (OM1, 2, 3, 4)	SM	MM
	UPC	APC	UPC/APC	UPC	UPC
Operating Wavelength(nm)	1310-1550		850-1300	1310-1550	850-1300
Insertion Loss (dB)	≤ 0.3	≤ 0.3	≤ 0.3	≤ 0.3	≤ 0.3
Return Loss (dB)	≥ 55	≥ 60	≥ 35	≥ 50	≥ 35
Repeatability (dB)	≤ 0.1	≤ 0.1	≤ 0.1	≤ 0.1	≤ 0.1
Interchangeability (dB)	≤ 0.2	≤ 0.2	≤ 0.2	≤ 0.2	≤ 0.2
Tensile Strength (N)	≥ 1000	≥ 1000	≥ 1000	≥ 1000	≥ 1000
Operating Temperature (°C)	-20 ~ +85	-20 ~ +85	-20 ~ +85	-20 ~ +85	-20 ~ +85
Storage Temperature (°C)	-40 ~ +85	-40 ~ +85	-40 ~ +85	-40 ~ +85	-40 ~ +85

Zion Communication's Hot Fiber Optic Connector

Zion Code	Zion Description
7234001	LC SX 0.9mm Pre-polished Ferrule Field Assembly Fiber Optic Connector
7234002	LC DX 2.0mm Pre-polished Ferrule Field Assembly Fiber Optic Connector
7234003	LC Uniboot Fiber Optic Connector
7234004	SC 0.9mm Pre-polished Ferrule Field Assembly Fiber Optic Connector
7234005	SC 2.0/3.0mm Pre-polished Ferrule Field Assembly Fiber Optic Connector
7234006	SC APC Flat Drop Cable Fiber Optic Connector
7234007	FC 0.9mm Pre-polished Ferrule Field Assembly Fiber Optic Connector
7234008	FC 2.0/3.0mm Pre-polished Ferrule Field Assembly Fiber Optic Connector
7234009	ST 0.9mm Pre-polished Ferrule Field Assembly Fiber Optic Connector
7234010	ST 2.0/3.0mm Pre-polished Ferrule Field Assembly Fiber Optic Connector
7234011	MU 0.9mm Series Fiber Optic Connector
7234012	MTRJ Series Fiber Optic Connector
7234013	E2000 0.9mm Series Fiber Optic Connector
7234014	MPO Series Fiber Optic Connector
7234015	FAST Field Series FC Fiber Optic Connector
7234016	FAST Field Series SC Fiber Optic Connector
7234017	FAST Field Series LC Fiber Optic Connector
7234018	FAST Field FC Hot-Melt Fiber Optical Connector
7234019	LC Pre-embedded Fast Connector
7234020	LC Straight-through Fast Connector
7234021	SC APC Hot-Melt Fast Connector
7234022	SC UPC Hot-Melt Fast Connector

Connector Type	LC, SC, FC, ST, MU, MTRJ, MPO, E-2000
	<p>LC (Lucent Connector/Little Connector/Local Connector) Typical Application: High density connections, SFP and SFP+ transceivers, XFP transceivers</p>
	<p>SC (Subscriber Connector/Square Connector/Standard Connector) Typical Application: Telecom, GPON, EPON, GBIC</p>
	<p>FC (Ferrule Connector) Typical Application: Datacom, telecom, measurement, equipment, single mode lasers</p>
	<p>ST (Straight Tip) Typical Application: Datacom</p>

OEM/ODM service for you

ZION Communication has rich experiences in producing OEM/ODM cases because of

- Customized Logo
- Label/PE bag/Carton design